



Phone: 519-323-4433
www.vikingcives.com
42626 Grey Rd 109
Mt Forest, ON
N0G 2L0

PRICE QUOTATION

QUOTE #: PM24-01126

DATE: nov26 2024

PROPOSED SHIP DATE: subject to chassis avail

TERMS: Net 30 days.

F.O.B.: Mount Forest, ON.

SALES PERSON: P.Milne

TO: Township of Huron Kinloss
ATTN: John Yungblut
RE: 2025 Tandem Axle Plow Budget

The above-quoted delivery time is the best known at time of tender call / quotation and is subject to change based upon shop loading at time of receipt of firm order to Viking-Cives Ltd.

Viking-Cives Ltd. is pleased to supply this price quotation for the following equipment as described:

Front Plow & Options

VCL135HSE10, One Way Plow, 35" intake, 66" discharge height, 15' 10" overall length, 12' edge, 10' clearing path. (3/16" moldboard skin) Standard Features:

Heavy Duty Tubular Pushframe & 10 gauge Rolled Steel Construction: perfect for high speed rural and interstate plowing. Slotted trip lugs allow the plow to trip when encountering speed bumps and other road obstacles. Adjustable trip spring assembly provides safe tripping action in a variety of conditions. Adjustable moldboard angle for enhanced edge efficiency. Shear bolts on moldboard brace protect the plow components and truck. Adjustable push frame shoes. Standard cast steel nosepiece. Grade 70 lift chain. Safety cable installed from pushframe to moldboard.

- * 1/2 x 8 x 144" steel cutting edge, center punched
- * 3/4 x 6 x 144" carbide cutting edge (3 pcs 3/4 x 6 x 48"), bull nose
- * Carbide nose piece in lieu of cast steel
- * Qty (2) of Carbide 8" or 12" punch moldboard shoe (each)
- * LSS5000 2 row carbide push frame shoes (one pair) in lieu of cast steel
- * Quick attach plate and bar
- * Anti-Sail rubber snow deflector 1/2" x 12" kit c/w mounting hardware
- * Hydraulic tilt moldboard w/ moldboard angle indicator rod, QD connectors & 3 x 6 tilt cylinder
- * 36" Plow marker whip, fluorescent orange
- * Baril DCC-181 Finish w/ corrosion protection: Medium gloss black
- * Spring retaining kit
- * Hi vis green 3M reflective tape on intake gusset

VCL Low Power Mount for standard plow and/or wing includes pushframe wing/post assembly, hydraulic lock pins and 1/2" tailplate/chassis mounting kit. Plow dampening accumulator kit included. Plow light mounting brackets included.

- * Cut O.E.M. front bumper and re-install ends to chassis.

- * *Plow dampening accumulator kit*
- * *Quick attach pockets and pins*
- * *Grote LED plow lights (HEATED) c/w integrated signal lights*
- * *LPM pushframe low light mounting assembly in lieu of standard LPM plow light mounting brackets*
- * *Medium gloss black (wing towers, harness)*

VCL350 SCL Cable lift tower with integrated back of cab hydraulic oil tank. Includes frame mount, front post, and rear wing tower. Does not include pusharms or moldboard.

- * *12" Convex heated mirror*
- * *12" raised angle iron bracket to mount Mirror adj offset*
- * *Viking tube style frame cross member*
- * *Aeon rubber helper spring assembly.*
- * *Dual adjustable needle valves for Rear Wing rate control of UP/DN*
- * *Rear wing harness mounted heated 5" Square, 3000 Lumen, LED floodlight*
- * *Height adjustable dual light mounting kit - mounted to front post (lights not included)*
- * *Qty (2) of Front post mounted heated 5" Square, 3000 Lumen, LED spotlight*
- * *Baril DCC-181 Finish w/ corrosion protection : Medium gloss black*

VCL144WHD 12' moldboard c/w pusharms. Ultra heavyduty ribbed construction for extreme conditions. Pre-Punched cutting edge holes for easy blade installation.

- * *5/8 x 6 x 132" (one piece blade) high wear wing blade*
- * *V45-1 curb shoe (each)*
- * *Baril DCC-181 Finish w/ corrosion protection : Medium gloss black (wing moldboard)*
- * *Parking leg for AHW wing*
- * *36" Plow marker whip, fluorescent orange*
- * *Conspicuity safety reflective tape on wing arms and on rear edge of wing.*
- * *Install a wing nose pc*

PL1415HW-II 12.5 cu yd water level capacity (15.4 cu yd w/ 10" sideboards)

Standard Features:

U-Style Design - Continuous roll formed sides with no brakes for optimal material flow to main conveyor. Specifically designed for sand, salt and aggregate material spreading. Self tensioning chain ensures that the chain is functioning properly, regardless of wear. Front discharge. Double acting tailgate for carrying large items. Air tailgate release for easy material dumping. Body prop dump hinge for safety checks. Durable 3/16" corten sides resist material wear & corrosion. Trunnion mount hoist cylinder.

** AR450 high tensile body construction. (HW-II, LW-II) (conveyor cover remains standard rubber for HW-II and LW-II) AR450 is an abrasion-resistant steel with a nominal hardness of 450 HBW. AR450 combines good bendability and weldability with an option for guaranteed impact toughness. Provides better dent and abrasion resistance as well as longer wear life, so you can achieve even greater savings. Yield strength is around 175,000 psi , Tensile strength is around 203,000 psi.*

- * *Asphalt door in tailgate (Hardox body)*

- * Shovel holder installed on driver's side front - to match body construction
- * Main conveyor sensor motor in lieu of standard 6 cu. in. w/o adapter cable
- * Pinned removable aluminum fenders attached to body instead of chassis (SA only)
- * Red/white 2" reflective tape along body fenders & across bottom tailgate
- * Main Conveyor cover clean out screen to be 'PINNED', not bolt on
- * Aluminium ladder in lieu of standard ladder LHF pinless
- * Grote "Ultra Blue Seal" - LED body lighting kit c/w license plate lamp, LH and RH 2-1/2" round red LED rear clearance, 6" oval LED back-up, 2 x 6" oval red LED stop/turn/tail, front side 2-1/2" marker lights.
- * LH & RH Corner post grote T26 LED" flood light pointed at ground and mounting bracket - hooked into reverse circuit switched for work
- * Grote blue self flashing 4" round LED strobe w/ stainless steel mount box
- * Qty (2) of Grote amber self flashing 4" round LED strobe w/ stainless steel mount box
- * Grote blue self flashing LED 6" corner post strobe
- * Qty (2) of Grote amber self flashing LED 6" corner post strobe
- * Removable Upper red assembly - Side mount led aluminium blue/amber w/ 2 x 4" red, 2 x 7" red, 1 x 4" blue strobe (LH) & 1 x 4" amber strobe (RH).
- * Single spinner - reversible belt cross conveyor for LW & HW body (includes spill shields)
- * Spinner clean off/anti coning device
- * RH material chute for reversible cross conveyor
- * Poly lined chutes in lieu of standard
- * Extended Cross Conveyor Poly Guards
- * Stainless steel cross conveyor upcharge includes frame and chutes
- * Qty (2) of Cross conveyor mounted heated 5" square, 3000 lumen, LED floodlight c/w mounting bracket and wiring harness
Mounting location: curb side, BOC, drivers side
- * VCL manufactured air tarp kit for 13' & 14' Prolines (less tarp cover) c/w rolled aluminium tarp arms
- * Mesh tarp cover 12 to 14 ft Prolines
- * 10" black poly sideboards - Pair
- * Dupont Imron Elite Finish w/ chromate epoxy Dupont CR2580 primer : VCL labour to paint body requires accurate paint code
- * LineX – Integral fender slopes & forward facing rear corner posts
- * Auto tension door pinned & stainless
- * 2nd ambers shipped loose
- * Lock nuts on upper red light brackets

Chassis Options

- * tow apron dump body hinge pintle combination with bracing and two D-rings, rated for maximum 45,000lbs is for class 8 single axle chassis c/w Baril DCC-181 finish - black
- * SWS 16399 amber/blue LED mini-bar
- * Pedestal mount for beacon light (with light mounting plate): cable tower (BOC hyd. tank)
- * Rear mounted T26 LED" floodlight for work light or backup light c/w bracket

- * Do not re-install OEM tail lights and ship loose
- * Stainless steel hinged chassis cover (proline bodies include a standard poly return cover)
- * Deduct for standard poly return cover on Proline body
- * Freight to ship plow wing to customers location
- * Tailgate checker kit for Proline Body

Air Electric Hydraulic Controls

- * RBE Groeneveld Auto Greaser
 - * RBE rev camera
 - * Sauer Danfoss 90cc crank mount piston pump
 - * VCL low oil override in cab console
 - * VCL Low oil level indicator w/ in cab warning light
 - * Standard hydraulic oil
 - * Ikron high pressure filter ass'y w/10 micron absolute filter
 - * Sauer Danfoss PVG32 series 1st section c/w inlet and outlet sections
 - * Qty (7) of Sauer Danfoss PVG32 series Remaining sections per section
 - * Qty (8) of VCL Standard 2 wire Hydraulic hose and hose ends by number of sections
Aeroquip 100R16 2 Wire EC215 with brazen resistant cover
 - * Stainless steel hydraulic lines - per truck (2 x lines for body/ 2 x lines for chassis) - for conveyor and spinner functions
 - * Black Partec hose wrap (seat belt material) not kevlar
 - * Stainless Steel Hose Hanger in lieu of Standard
 - * Valve enclosure assembly - SCL 10 Section (SSTL)
 - * Bosch Rexroth CS660 spreader control c/w 2 section valve block/c/w cabling harness
 - * Bosch Main Conveyor Motor sensor feedback cable
 - * Sprage Road Watch SS Road Temp sensor with interface to Bosch Controller
 - * Body up indicator c/w in cab warning light and chime
 - * New cab console auxiliary switch box, includes 16 illuminated push buttons to control lighting. HQ520 electrical system.
 - * Integrated control console assembly
 - * Qty (4) of Standard RMH Air Control: \LIFT \FWING \WSLIDE \TILT.PLOW
 - * Lift To Lock RMH Air Control: \HOIST
 - * Standard RMH Air Control: \TILT.HITCH
 - * Qty (2) of Air Switches: \TAIL \TARP
 - * Cab floor stiffener plate
- NET INSTALLED \$198,430.00ea**

International 2026 HV615 Tandem Axle Cab & Chassis

NET \$224,300.00ea

**all as per included build sheets*

TOTAL:.....**\$422,730.00** (each + tax)

**** NOTES FOR THE ABOVE-QUOTED EQUIPMENT ****

- 1) The price and terms on this quotation are not subject to verbal changes or other agreements unless approved in writing by the home office of the seller. All quotations and agreements are contingent upon strikes, accidents, fires, availability of material and all other causes beyond our control. Prices are based on cost and conditions existing on the date of quotation and are subject to changes by the seller before final acceptance.
- 2) Typographical and stenographic errors are subject to correction.
- 3) Conditions not specifically stated herein shall be governed by the established trade customs. Terms inconsistent with those stated herein which may appear on purchaser's final order will not be binding on the Seller.
- 4) Quoted delivery time: The above-quoted delivery time is the best known at time of tender call / quotation and is subject to change based upon shop loading at time of chassis arrival and / or receipt of firm order to Viking-Cives, Mount Forest, Ontario.
- 5) **Chassis requirements:**
 - Chassis specifications must be approved by Viking-Cives Engineering Department prior to acceptance of order.
 - Additional charges are applicable if any modifications in lighting/wiring connections are required.
 - Fully powered chassis OEM plow light connections are required.
 - Electrical connections, body builders plug in's etc., to be provided with chassis (back of cab or inside) to allow installation of auxiliary lighting and electrical connections. High amp system required.
 - Quoted prices **do not** include alteration or relocation of exhaust, battery box, air dryer, or fuel tank etc.
 - Road Speed: In-cab provision for spreader control system to pick up road speed is required.
 - Customer to ensure chassis to be supplied is suitable for installation & operation of equipment quoted. Any possible required chassis modifications **are not** included in quoted price.
- 6) Chassis delivery from VCL **is NOT** included in the above-quoted price.
- 7) Delivery of plow and / or wing to customer's yard is included in the above price.
- 8) Auto lubrication system **is** included in the above price.
- 9) Back-up camera system **is** included in the above price.

ALL APPLICABLE TAXES ARE EXTRA.

QUOTE VALID FOR 30 DAYS.

Respectfully Submitted,

Paul Milne

Regional Sales Manger